

Pana 21:9 Displays

Pana 105 Touch
Pana 105 Non-Touch

Pana 81 Touch
Pana 81 Non-Touch



Pana 21:9 Displays

- **21:9 in native 5K resolution**
- **Touch and Non-Touch versions**

See the World through a 21:9 Lens

Pana's 21:9 ultra-wide 5K resolution brings a refreshing form factor to the conventional display market. Our 8-foot wide Pana 105 canvas optimizes team productivity allowing for improved interaction and work place collaboration.

The market most receptive to this format are enterprise and industrial companies leaning into visualization technology to be their focal point and center piece. CIOs are telling us 21:9 is making the biggest impressions enabling them to stand out, land new clients and attract better talent. That's a win-win.

Lightweight and maneuverable, the Pana is ideal for retrofits as all sizes fit into a commercial service elevator and can be mounted using standard industry hardware without reinforced concrete or steel backing. Pana's lower infrastructure costs equates to a lower cost of ownership as a result of easy retrofit, reduced energy consumption and affordable price point.

PANA FEATURES

21:9 Panoramic

The extra wide form factor is inspired by our natural human ability to see wider than we see taller.

5K Resolution

Pana provides 33% more pixels with 5K resolution giving the user more real estate in which to work.

Interactive User Experience

Touch enables the expectation for interactive autonomy, speed and ease-of-use. Pana interactive displays are touch driven by multiple, simultaneous collaborators.

Built for Human Interaction

More pertinent information gets placed in our visual sweet spot increasing our comprehension and productivity. And all the pixels are placed where everyone on the team can reach them preserving our dignity among our peers of not having to overreach or bend over to interact with the display.

Pana 21:9 Displays Specifications

	Pana 105 Touch	Pana 105 Non-Touch	Pana 81 Touch	Pana 81 Non-Touch
SPECIFICATIONS				
Model Name	Pana 105T	Pana 105D	Pana 81T	Pana 81D
Resolution	5120 x 2160	5120 x 2160	5120 x 2160	5120 x 2160
Orientation	Landscape or Portrait	Landscape or Portrait	Landscape or Portrait	Landscape or Portrait
Screen Size	105" (2667mm) diagonal	105" (2667mm) diagonal	81" (2057mm) diagonal	81" (2057mm) diagonal
Contrast Ratio	10 000:1	10 000:1	10 000:1	10 000:1
Brightness	700 cd/m²	700cd/m²	700 cd/m²	700 cd/m²
Refresh Rate	60Hz	60Hz	60Hz	60Hz
Viewing Angle	178° H/V	178° H/V	178° H/V	178° H/V
Lifetime	≥ 50,000 Hrs	≥ 50,000 Hrs	≥ 50,000 Hrs	≥ 50,000 Hrs
Response Time	8 ms	8 ms	8 ms	8 ms
Display	21:9 aspect ratio, anti-glare, IPS LCD with local dimming, direct-bonding IR with 20 simultaneous touch points	21:9 aspect ratio, anti-glare, IPS LCD with local dimming	21:9 aspect ratio, anti-glare, IPS LCD with local dimming, bezel-less metal-mesh capacitive with 20 simultaneous touch points	21:9 aspect ratio, anti-glare, IPS LCD with local dimming
HDCP Support	2.2	2.2	2.2	2.2
POWER				
Input Current	100-240 VAC 60/50 Hz 6Amp	100-240 VAC 60/50 Hz 6Amp	100-240 VAC 60/50 Hz 6Amp	100-240 VAC 60/50 Hz 6Amp
Power Standby	0.5 Watts	0.5 Watts	0.5 Watts	0.5 Watts
Internal Speaker Output	2 x 15 Watts	2 x 15 Watts	2 x 15 Watts	2 x 15 Watts
Typical Power Consumption	333 Watts	312 Watts	298 Watts	302 Watts
Max Power Consumption	600 Watts	600 Watts	500 Watts	500 Watts
USB-C PD Output	65 Watts	65 Watts	65 Watts	65 Watts
Operating Temperature	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)	32° - 104°F (0° - 40°C)
CONNECTIVITY				
DisplayPort 1.4 In	1	1	1	1
DisplayPort 1.4 Out	1 (MST)	1 (MST)	1 (MST)	1 (MST)
HDMI 2.0 In	2	1	2	1
USB-C	1	1	1	1
USB 2.0 Type-A	3 Public, 4 Private for USB-C input	3 Public, 4 Private for USB-C input	3 Public, 4 Private for USB-C input	3 Public, 4 Private for USB-C input
3.5mm Line Out	1	1	1	1
S/PDIF Optical Fiber	1	1	1	1
Ethernet/RS232	1	1	1	1
OPS Slot	JAE TX-25A	JAE TX-25A	JAE TX-25A	JAE TX-25A
ACCESSORIES				
Ships With	Power cable, remote control	Power cable, remote control	Power cable, remote control	Power cable, remote control
Pana OPS (Optional)	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.	i7, 16GB DDR4, 256GB (NVME), LAN, Wi-Fi, Bluetooth, Type-C.
Pana Pen (Optional)	Active Smart Pen, Pen & Windows Ink support.		Active Smart Pen, Pen & Windows Ink support.	
DIMENSIONS				
Dimensions	99.2" x 43.5" x 4.3" (2520mm x 1105mm x 109mm)	97.9" x 42.2" x 3.9" (2487mm x 1072mm x 99mm)	76.1" x 33.4" x 3.4" (1933mm x 847mm x 86mm)	75.6" x 32.7" x 3.3" (1919mm x 830mm x 83mm)
Weight	207 lbs (94 kg)	135.5 lbs (61.5 kg)	117 lbs (53 kg)	77 lbs (35 kg)
Shipping Dimensions	109.4" x 59" x 13" (2780mm x 1500mm x 330mm)	105.5" x 55.1" x 12.6" (2680mm x 1400mm x 320mm)	84.4" x 40.0" x 10.3" (2145mm x 1015mm x 262mm)	84.4" x 40.0" x 10.3" (2145mm x 1015mm x 262mm)
Shipping Weight	258 lbs (117 kg)	192 lbs (87 kg)	141 lbs (64 kg)	105 lbs (47 kg)
Mount Dimensions	1500mm x 600mm	1500mm x 600mm	800mm x 400mm	800mm x 400mm
CERTIFICATIONS				
Regulatory and Safety Certifications	cULus, FCC, RoHS CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS	cULus, FCC, RoHS CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS, Display HDR 400	cULus, FCC, RoHS, CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS	cULus, FCC, RoHS, CEC, CA65, CE, ErP, REACH, WEEE, UKCA, IECEE, SAA, RCM, GEMS, PSE, VCCI, PSB, CCC, INMETRO, NOM, BIS

Pana 105 shown in Landscape and Portrait orientation.



jupiter.com

© 2025 Jupiter. Jupiter is a registered trademark of Jupiter Systems, Inc. Product specifications and designs are subject to change without notice. All brand and products names and logos are registered trademarks of Jupiter Systems, Inc.

DS_PANA_SEPT2025